

# Prilog 10

---

Živčić, Juraj

## Supplement / Prilog

Publication year / Godina izdavanja: **2016**

Permanent link / Trajna poveznica: <https://urn.nsk.hr/urn:nbn:hr:128:386005>

Rights / Prava: [In copyright](#) / [Zaštićeno autorskim pravom](#).

Download date / Datum preuzimanja: **2025-03-12**



**VELEUČILIŠTE U KARLOVCU**  
Karlovac University of Applied Sciences

Repository / Repozitorij:

[Repository of Karlovac University of Applied  
Sciences - Institutional Repository](#)

|   |  |   |  |  |  |
|---|--|---|--|--|--|
| Builder :<br>Sprinkler d.o.o.<br>Vocarska cesta 112<br>Zagreb |  | Mode of operation : 3. kat<br><input checked="" type="checkbox"/> wet system<br><input type="checkbox"/> dry system<br><input type="checkbox"/> fast dry system<br><input type="checkbox"/> prior driven dry system<br><input type="checkbox"/> tandem system |  | BG : OH2<br>Effective area:<br><input type="checkbox"/> favourable<br><input checked="" type="checkbox"/> least favourable |  |
| Operator :<br>Sprinkler d.o.o.                                |  | Roughness of pipes (C-value) 20   |  | Demand :<br><input checked="" type="checkbox"/> pressure at sprinkler<br><input type="checkbox"/> pump pressure            |  |
| Project-No. :<br>418-14                                       |  | Supply of hydrants with water :   |  | Use of pipes according to DIN 2440<br>l/min at node No. Strangrohr-No. : 0 ; Sprinkler-No. : 0                             |  |
| Person in charge :<br>BS                                      |  | Height of storage (m)<br>min. water admission (mm/min)<br>real effective area (ea) (m²)<br>max. protection area/sprinkler in ea (m²)<br>No. of sprinklers / effecton area   |  | Ceiling protec. Rack protec.<br>3,70<br>8,10<br>143,50<br>12,10<br>16  |  |
| Date :<br>11.2014.  |  | No. of additional sprinkler / effecton area<br>hydraulic considered no. of sprinkler<br>no. of protected decks<br>biggest distance of sprinkler (m)   |  | 1<br>4,60  |  |
| Object :<br>TC Trogir   |  |   |  |  |  |

|  |         |         |         |       |                          |
|--|---------|---------|---------|-------|--------------------------|
| Demand press required / Supply press available / cushion       | [bar]   | 5,045   | 5,858   | 0,813 | according Hazen-Williams |
| Water rate at point to feed in / Pump                          | [l/min] | 1202,32 | 1372,52 |       |                          |
| hydraulic unfavourabelst sprinkler in the effective area       |         |         |         |       |                          |
| No. of pipe / Sprinkler-No.                                    |         | 1 / 3   |         |       |                          |
| minimum pressure / Required density                            | [bar]   | 0,825   | 72,657  |       |                          |
| geodetic difference in height sprinkler - point to feed        | [m]     | 22,40   |         |       |                          |
| geodetic difference in height lowest sprinkler - point to feed | [m]     | 22,40   |         |       |                          |
| max. pressure of sprinkler in the effective area               | [bar]   | 1,415   |         |       |                          |
| min. pressure of sprinkler in the effective area               | [bar]   | 0,825   |         |       |                          |
| max. water speed in the effective area                         | [m/s]   | 3,25    |         |       |                          |
| No. of sprinkler in the effective area                         |         | 16      |         |       |                          |



| Name   | Beg-<br>node | End-<br>node | Pobj<br>[bar] | K     | Q <sub>spine</sub><br>[l/min] | Q <sub>branch</sub><br>[l/min] | dia-<br>meter | C-Value | length<br>of pipe<br>[m] | Fittings<br>BWV/T/TA/VA/NAV/SV/K<br>kind and no | hydraulic<br>total length<br>[m] | Δ p<br>friction<br>[bar/m] | difference<br>in height<br>[m] | Δ p<br>total<br>[bar] | Pend<br>[bar] | v<br>[m/s] | remarks |
|--------|--------------|--------------|---------------|-------|-------------------------------|--------------------------------|---------------|---------|--------------------------|---|----------------------------------|----------------------------|--------------------------------|-----------------------|---------------|------------|---------|
| R 6-1  | 44           | 43           | 1,572         |       |                               | -43,1                          | DN 32         | 120     | 40,50                    | 2B+2T   | 45,30                            | -0,0024                    |                                | -0,1100               | 1,462         | 0,71       |         |
| R 5-1  | 42           | 41           | 1,552         |       |                               | -39,5                          | 32            | 120     | 43,00                    | 2T  | 46,60                            | -0,0021                    |                                | -0,0962               | 1,455         | 0,65       |         |
| R 4-2  | 40           | 38           | 1,545         |       |                               | -62,1                          | 32            | 120     | 25,30                    | 1T  | 27,10                            | -0,0048                    |                                | -0,1294               | 1,415         | 1,02       |         |
| R 4-S1 | 39           | 38           | 1,415         | 80,00 | 95,2                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 1,415         |            |         |
| R 4-1  | 38           | 37           | 1,415         |       |                               | 33,1                           | 32            | 120     | 18,50                    | 2B+1T   | 21,50                            | 0,0015                     |                                | 0,0321                | 1,447         | 0,54       |         |
| R 3-6  | 36           | 34           | 1,541         |       |                               | -171,9                         | 32            | 120     | 19,60                    | 1T  | 21,40                            | -0,0314                    |                                | -0,6725               | 0,869         | 2,83       |         |
| R 3-S1 | 35           | 34           | 0,868         | 80,00 | 74,6                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,869         |            |         |
| R 3-5  | 34           | 32           | 0,869         |       |                               | -97,4                          | 32            | 120     | 2,40                     | 2B  | 3,60                             | -0,0110                    |                                | -0,0395               | 0,829         | 1,60       |         |
| R 3-S1 | 33           | 32           | 0,829         | 80,00 | 72,8                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,829         |            |         |
| R 3-4  | 32           | 30           | 0,829         |       |                               | -24,5                          | 32            | 120     | 2,60                     |   | 2,60                             | -0,0009                    |                                | -0,0022               | 0,827         | 0,40       |         |
| R 3-S1 | 31           | 30           | 0,827         | 80,00 | 72,7                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,827         |            |         |
| R 3-3  | 30           | 28           | 0,827         |       |                               | 48,2                           | 32            | 120     | 3,80                     |   | 3,80                             | 0,0030                     |                                | 0,0114                | 0,838         | 0,79       |         |
| R 3-S1 | 29           | 28           | 0,838         | 80,00 | 73,2                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,838         |            |         |
| R 3-2  | 28           | 26           | 0,838         |       |                               | 121,5                          | 32            | 120     | 3,80                     |   | 3,80                             | 0,0165                     |                                | 0,0628                | 0,901         | 2,00       |         |
| R 3-S1 | 27           | 26           | 0,901         | 80,00 | 75,9                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,901         |            |         |
| R 3-1  | 26           | 25           | 0,901         |       |                               | 197,4                          | 32            | 120     | 11,55                    | 1T  | 13,35                            | 0,0406                     |                                | 0,5418                | 1,443         | 3,25       |         |
| R 2-6  | 24           | 22           | 1,539         |       |                               | -171,8                         | 32            | 120     | 19,60                    | 1T  | 21,40                            | -0,0314                    |                                | -0,6718               | 0,867         | 2,83       |         |
| R 2-S1 | 23           | 22           | 0,867         | 80,00 | 74,5                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,867         |            |         |
| R 2-5  | 22           | 20           | 0,867         |       |                               | -97,3                          | 32            | 120     | 2,40                     | 2B  | 3,60                             | -0,0110                    |                                | -0,0395               | 0,828         | 1,60       |         |
| R 2-S1 | 21           | 20           | 0,827         | 80,00 | 72,8                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,828         |            |         |
| R 2-4  | 20           | 18           | 0,828         |       |                               | -24,6                          | 32            | 120     | 2,60                     |   | 2,60                             | -0,0009                    |                                | -0,0022               | 0,825         | 0,40       |         |
| R 2-S1 | 19           | 18           | 0,825         | 80,00 | 72,7                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,825         |            |         |
| R 2-3  | 18           | 16           | 0,825         |       |                               | 48,1                           | 32            | 120     | 3,80                     |   | 3,80                             | 0,0030                     |                                | 0,0113                | 0,837         | 0,79       |         |
| R 2-S1 | 17           | 16           | 0,837         | 80,00 | 73,2                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,837         |            |         |
| R 2-2  | 16           | 14           | 0,837         |       |                               | 121,3                          | 32            | 120     | 3,80                     |   | 3,80                             | 0,0165                     |                                | 0,0626                | 0,899         | 2,00       |         |
| R 2-S1 | 15           | 14           | 0,899         | 80,00 | 75,9                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,899         |            |         |
| R 2-1  | 14           | 13           | 0,899         |       |                               | 197,2                          | 32            | 120     | 11,55                    | 1T  | 13,35                            | 0,0405                     |                                | 0,5406                | 1,440         | 3,25       |         |
| R 1-6  | 12           | 10           | 1,538         |       |                               | -171,8                         | 32            | 120     | 19,60                    | 1T  | 21,40                            | -0,0314                    |                                | -0,6716               | 0,867         | 2,83       |         |
| R 1-S1 | 11           | 10           | 0,867         | 80,00 | 74,5                          |                                | 15            | 120     |                          |   |                                  |                            |                                |                       | 0,867         |            |         |
| R 1-5  | 10           | 8            | 0,867         |       |                               | -97,3                          | 32            | 120     | 2,40                     | 2B  | 3,60                             | -0,0110                    |                                | -0,0395               | 0,827         | 1,60       |         |

| Name   | Beg-<br>node | End-<br>node | P <sub>beg</sub><br>[bar] | K     | Q <sub>design</sub><br>[l/min] | Q <sub>design</sub><br>[l/min] | dis-<br>meter | C-Value | length<br>of pipe<br>[m] | Fittings<br>BW/IT/TA/VNAV/SA/K<br>kind and no | hydraulic<br>total length<br>[m] | $\Delta p$<br>friction<br>[bar/m] | difference<br>in height<br>[m] | $\Delta p$<br>total<br>[bar] | Pend<br>[bar] | v<br>[m/s] | remarks |
|--------|--------------|--------------|---------------------------|-------|--------------------------------|--------------------------------|---------------|---------|--------------------------|---|----------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------|------------|---------|
| R 1-S1 | 9            | 8            | 0,827                     | 80,00 | 72,8                           | 72,8                           | 15            | 120     |                          |   |                                  |                                   |                                |                              | 0,827         |            |         |
| R 1-4  | 8            | 6            | 0,827                     |       |                                | -24,6                          | 32            | 120     | 2,60                     |   | 2,60                             | -0,0009                           |                                | -0,0022                      | 0,825         | 0,40       |         |
| R 1-S1 | 7            | 6            | 0,825                     | 80,00 | 72,7                           | 72,7                           | 15            | 120     |                          |   |                                  |                                   |                                |                              | 0,825         |            |         |
| R 1-3  | 6            | 4            | 0,825                     |       |                                | 48,1                           | 32            | 120     | 3,80                     |   | 3,80                             | 0,0030                            |                                | 0,0113                       | 0,836         | 0,79       |         |
| R 1-S1 | 5            | 4            | 0,836                     | 80,00 | 73,2                           | 73,2                           | 15            | 120     |                          |   |                                  |                                   |                                |                              | 0,836         |            |         |
| R 1-2  | 4            | 2            | 0,836                     |       |                                | 121,3                          | 32            | 120     | 3,80                     |   | 3,80                             | 0,0165                            |                                | 0,0626                       | 0,899         | 2,00       |         |
| R 1-S1 | 3            | 2            | 0,899                     | 80,00 | 75,8                           | 75,8                           | 15            | 120     |                          |   |                                  |                                   |                                |                              | 0,899         |            |         |
| R 1-1  | 2            | 1            | 0,899                     |       |                                | 197,1                          | 32            | 120     | 11,55                    | 1T  | 13,35                            | 0,0405                            |                                | 0,5402                       | 1,439         | 3,25       |         |